

TAZ-4H 4 Zone Add-A-Zone Panel Kit



Use the Add-A-Zone panel with HZ432K zone panel kit for systems over 4 zones. Each TAZ-4H can add an additional 4 zones for a maximum of 32 zones. A separate transformer is recommended for each TAZ-4H.

THERMOSTATS

The TrueZONE panels are compatible with virtually any thermostat you would normally use for the same system when not zoned. We have highlighted some different Resideo thermostats in the following section.

TH6320R1004 Wireless FocusPRO Thermostat



Programmable wireless FocusPRO thermostat used with HZ322 (2-3 zone) or HZ432 (2-4 zone) and *THM4000 wireless adapter for wireless zoning systems.

- Installs with no wires at the thermostat.
- 5-1-1 programmability.
- Large backlit display.
- Easy-access battery replacement.
- Standard thermostat pricing and warranty apply to this thermostat.
- Compatible with RedLINK Gateway, wireless outdoor sensor, or portable comfort control (page 6).

YTH6320R1023

Kit with TH6320R1004 thermostat and *THM4000R1000 wireless adapter. Use one kit with HZ322 for 2-3 zone systems or HZ432 for 2-4 zone systems. Use TH6320R1004 thermostats for zone 2-4.

TH5320R1002 Wireless FocusPRO Thermostat



Non-programmable wireless FocusPRO thermostat used with HZ322 (2-3 zone) or HZ432 (2-4 zone) and *THM4000 wireless adapter for wireless zoning systems.

- Installs with no wires at the thermostat.
- Non-programmable.
- Large backlit display.
- Easy-access battery replacement.
- Standard thermostat pricing and warranty apply to this thermostat.
- Compatible with RedLINK Gateway, wireless outdoor sensor, or portable comfort control (page 6).

YTH5320R1025

Kit with TH5320R1002 thermostat and THM4000R1000* wireless adapter. Use one kit with HZ322 for 2-3 zone systems or HZ432 for 2-4 zone systems. Use TH5320R1002 thermostats for zone 2-4.

RedLINK VisionPRO Thermostats



Programmable wired or wireless VisionPRO thermostats used with any TrueZONE panel when wired or with HZ432 and HZ322 and THM4000 wireless adapter for wireless zoning.

- Touch screen display.
- Installs with wires or no wires at the thermostat (THM5421R1021 EIM or THM4000 adaptor + HZ322/HZ432 needed when wireless*).
- 7-day programmability.
- 10 sq. in. backlit display.
- Standard thermostat pricing and warranty apply to this thermostat.

* See RedLINK accessories on page 6 for compatibility notes.

* If THM5421R1021 EIM is used, a separate EIM is needed for each thermostat and each EIM needs to be spaced at least 2 feet apart.

TH8110R1008

One stage heat and cooling. Can be either wired at sub-base or wireless to *THM4000R1000 adapter + HZ322 or HZ432 zone panel.

*NOTE: The THM4000R cannot be used for systems over 4 zones. A separate THM5320R1000 EIM is needed for each RedLINK FocusPRO on systems over 5 zones. A separate THM5421R1021 EIM is needed for each RedLINK VisionPRO on systems over 5 zones.